


Malleable iron 90° straight elbow

Malleable iron 90° straight elbow, precise right-angle steering, tough and impact-resistant, suitable for rapid industrial pipeline connection.



- **Standard:** ANSI/ASME B16.3
UL/FM
- **Material:** Malleable iron ASTM A197
- **Thread:** NPT
- **W. pressure:** Class 150, 300 psi (-29°C to 66°C)
Class 300, 1000 / 1500 / 2000 psi (-29°C to 66°C)
- **Surface:** Black iron / hot dip galvanized
- **Size Range:** 3/8" ---6" (Class 150)
1/4" ---4" (Class 300)



Available size(Class 150)

SIZE			A
INCH	DN	MM	MM
3/8"	10	17.1	24.1
1/2"	15	21.3	28.5
3/4"	20	26.7	33.3
1"	25	33.4	38.1
1-1/4"	32	42.2	44.5
1-1/2"	40	48.3	49.3
2"	50	60.3	57.2
2-1/2"	65	73	68.6
3"	80	88.9	78.2
4"	100	114.3	96.3
6"	150	168.3	130.3

Malleable iron 90° straight elbow

Available size(Class 300)

SIZE			A
INCH	DN	MM	MM
1/4"	8	13.7	23.9
3/8"	10	17.1	26.9
1/2"	15	21.3	31.8
3/4"	20	26.7	35.6
1"	25	33.4	41.4
1-1/4"	32	42.2	49.3
1-1/2"	40	48.3	54.1
2"	50	60.3	63.5
2-1/2"	65	73	74.7
3"	80	88.9	85.9
4"	100	114.3	114