


Grooved 90° reducing elbow with female threaded outlet

Grooved 90° reducing elbow with female threaded outlet is a 90-degree grooved reducing elbow. One end is grooved connection and the other end is an internal thread interface with different pipe diameters. It is used to simultaneously achieve pipe rotation, diameter change and connection with external thread components.



- Standard:** ANSI / UL 213C UL / FM
- Material:** Ductile iron ASTM A536, 65-45-12
- Thread run:** Female thread, NPT / BSPT
- Rated pressure:** 300 - 500 psi
- Surface:** Red painting / hot dip galvanized
- Size range:** 1-1/4"x1/2" - 3"x1"



Available size

Size			Center to end, L(mm)	
Inch	DN	mm	L1	L2
1-1/4" × 1/2"	32 × 15	42.4 × 21.3	35.1	44.5
1-1/4" × 3/4"	32 × 20	42.4 × 26.9	34.9	47.6
1-1/4" × 1"	32 × 25	42.4 × 33.7	38.1	51.6
1-1/2" × 1/2"	40 × 15	48.3 × 21.3	34.9	44.5
1-1/2" × 3/4"	40 × 20	48.3 × 26.9	34.9	47.6
1-1/2" × 1"	40 × 25	48.3 × 33.7	38.1	51.6
2" × 1/2"	50 × 15	60.3 × 21.3	41.4	44.5
2" × 3/4"	50 × 20	60.3 × 26.9	41.3	47.6
2" × 1"	50 × 25	60.3 × 33.7	44.5	51.6
2-1/2" × 3/4"	65 × 20	73.0 × 26.9	46	47.6
2-1/2" × 1"	65 × 25	73.0 × 33.7	49.2	51.6
3" × 3/4"	80 × 20	88.9 × 26.9	60.3	52.4
3" × 1"	80 × 25	88.9 × 33.7	63.5	52.4