


Grooved reducing tee with female threaded branch

Grooved reducing tee with female threaded branch is a reducing three-way pipe fitting. Its branch interface is designed with an internal thread and is used for the connection of reducing pipes and the branch installation of components that require internal thread connection



- Standard:** ANSI / UL 213C UL / FM
- Material:** Ductile iron ASTM A536, 65-45-12
- Type:** Short / Standard
- Branch:** Female thread, NPT / BSPT
- Rated pressure:** 300 - 500 psi
- Surface:** Red painting / hot dip galvanized
- Size range:** 1-1/4"×1" - 6"×3"



Available size

Size			Center to end (mm),Short		Center to end (mm),Standard	
Inch	DN	mm	L1	L2	L1	L2
1-1/4" × 1"	32 × 25	42.4 × 33.7	60	60	/	/
1-1/2" × 1"	40 × 25	48.3 × 33.7	60	60	/	/
1-1/2" × 1-1/4"	40 × 32	48.3 × 42.4	60	60	/	/
2" × 1"	50 × 25	60.3 × 33.7	70	70	83	83
2" × 1-1/4"	50 × 32	60.3 × 42.4	70	70	/	/
2" × 1-1/2"	50 × 40	60.3 × 48.3	70	70	/	/
2-1/2" × 1"	65 × 25	73.0 × 33.7	76	76	/	/
2-1/2" × 1-1/4"	65 × 32	73.0 × 42.4	76	76	95	95
2-1/2" × 1-1/2"	65 × 40	73.0 × 48.3	76	76	95	95
2-1/2" × 2"	65 × 50	73.0 × 60.3	76	76	/	/
2-1/2" × 1"	65 × 25	76.1 × 33.7	76	76	/	/
2-1/2" × 1-1/4"	65 × 32	76.1 × 42.4	76	76	/	/

Grooved reducing tee with female threaded branch

Available size

Size			Center to end (mm),Short		Center to end (mm),Standard	
Inch	DN	mm	L1	L2	L1	L2
2-1/2" × 1-1/2"	65 × 40	76.1 × 48.3	76	76	/	/
2-1/2" × 2"	65 × 50	76.1 × 60.3	76	76	/	/
3" × 1	80 × 25	88.9 × 33.7	86	86	108	108
3" × 1-1/4"	80 × 32	88.9 × 42.4	86	86	108	108
3" × 1-1/2"	80 × 40	88.9 × 48.3	86	86	/	/
3" × 2"	80 × 50	88.9 × 60.3	86	86	/	/
3" × 2-1/2"	80 × 65	88.9 × 76.1	86	86	/	/
4" × 1"	100 × 25	114.3 × 33.7	101	101	127	127
4" × 1-1/4"	100 × 32	114.3 × 42.4	101	101	/	/
4" × 1-1/2"	100 × 40	114.3 × 48.3	101	101	127	127
4" × 2"	100 × 50	114.3 × 60.3	101	101	127	127
4" × 2-1/2"	100 × 65	114.3 × 76.1	101	101	/	/
4" × 3"	100 × 80	114.3 × 88.9	101	101	127	127
5" × 1"	125 × 25	139.7 × 33.7	124	124	/	/
5" × 1-1/4"	125 × 32	139.7 × 42.4	124	124	/	/
5" × 1-1/2"	125 × 40	139.7 × 48.3	124	124	/	/
5" × 2"	125 × 50	139.7 × 60.3	124	124	/	/
5" × 2-1/2"	125 × 65	139.7 × 76.1	124	124	/	/
5" × 3"	125 × 80	139.7 × 88.9	124	124	/	/
6" × 1"	150 × 25	165.1 × 33.7	140	140	/	/
6" × 1-1/4"	150 × 32	165.1 × 42.4	140	140	/	/
6" × 1-1/2"	150 × 40	165.1 × 48.3	140	140	/	/
6" × 2"	150 × 50	165.1 × 60.3	140	140	/	/
6" × 2-1/2"	150 × 65	165.1 × 76.1	140	140	/	/
6" × 3"	150 × 80	165.1 × 88.9	140	140	/	/
6" × 1-1/4"	150 × 32	168.3 × 42.4	140	140	/	/
6" × 1-1/2"	150 × 40	168.3 × 48.3	140	140	/	/
6" × 2"	150 × 50	168.3 × 60.3	140	140	165	165
6" × 2-1/2"	150 × 65	168.3 × 76.1	140	140	/	/
6" × 3"	150 × 80	168.3 × 88.9	140	140	165	165