


Grooved reducing cross

Grooved reducing cross is a reducer four-way pipe fitting. The interface pipe diameters are not exactly the same and are distributed in a cross shape, which is used to achieve cross-shaped branch connections of pipelines with different pipe diameters.



- **Standard:** ANSI / UL 213C UL / FM
- **Material:** Ductile iron ASTM A536, 65-45-12
- **Rated pressure:** 300 - 500 psi
- **Surface:** Red painting / hot dip galvanized
- **Size range:** 2-1/2"×2" - 8"×6"



Available size

Size			Center to end(mm)	
Inch	DN	mm	L1	L2
2-1/2" × 2"	65 × 50	76.1 × 60.3	76	76
3" × 2"	80 × 50	88.9 × 60.3	86	86
4" × 2"	100 × 50	114.3 × 60.3	101	101
4" × 3"	100 × 80	114.3 × 88.9	101	101
5" × 4"	125 × 100	139.7 × 114.3	124	124
6" × 2"	150 × 50	165.1 × 60.3	140	140
6" × 2-1/2"	150 × 65	165.1 × 76.1	140	140
6" × 3"	150 × 80	165.1 × 88.9	140	140
6" × 4"	150 × 100	165.1 × 114.3	140	140
6" × 2"	150 × 50	168.3 × 60.3	140	140
8" × 2"	200 × 50	219.1 × 60.3	175	175
8" × 4"	200 × 100	219.1 × 114.3	175	175
8" × 5"	200 × 125	219.1 × 139.7	175	175
8" × 6"	200 × 150	219.1 × 165.1	175	175