


Grooved eccentric reducer

Grooved eccentric reducer is an eccentric reducer with different diameters at both ends and a deviated centerline. It is used in piping systems to connect pipes of different diameters and to prevent fluid accumulation or gas blockage



- **Standard:** ANS / UL 213C UL / FM
- **Material:** Ductile iron ASTM A536, 65-45-12
- **Rated pressure:** 300 - 500 psi
- **Surface:** Red painting / hot dip galvanized
- **Size range:** 2-1/2"×2" - 10"×8"



Available size

Size			Center to end, L(mm)	
Inch	DN	mm	Short	Long
2-1/2" × 2"	65 × 50	76.1 × 60.3	64	/
3" × 2"	80 × 50	88.9 × 60.3	64	89
3" × 2-1/2"	80 × 65	88.9 × 73.0	64	/
3" × 2-1/2"	80 × 65	88.9 × 76.1	64	/
4" × 2"	100 × 50	114.3 × 60.3	76	102
4" × 2-1/2"	100 × 65	114.3 × 73.0	76	/
4" × 2-1/2"	100 × 65	114.3 × 76.1	76	102
4" × 3"	100 × 80	114.3 × 88.9	76	102
5" × 2-1/2"	125 × 65	139.7 × 76.1	89	/
5" × 3"	125 × 80	139.7 × 88.9	89	/
5" × 4"	125 × 100	139.7 × 114.3	89	127
6" × 2-1/2"	150 × 65	165.1 × 76.1	102	/
6" × 3"	150 × 80	165.1 × 88.9	102	140

Grooved eccentric reducer

Available size

Size			Center to end,L(mm)	
Inch	DN	mm	Short	Long
6" × 4"	150 × 100	165.1 × 114.3	102	140
6" × 5"	150 × 125	165.1 × 139.7	102	140
6" × 3"	150 × 80	168.3 × 88.9	102	140
6" × 4"	150 × 100	168.3 × 114.3	102	140
6" × 5"	150 × 125	168.3 × 139.7	102	140
8" × 3"	200 × 80	219.1 × 88.9	127	/
8" × 4"	200 × 100	219.1 × 114.3	127	215
8" × 5"	200 × 125	219.1 × 139.7	127	/
8" × 6"	200 × 150	219.1 × 165.1	127	215
8" × 6"	200 × 150	219.1 × 168.3	127	215
10" × 6"	250 × 150	273.0 × 165.1	152	/
10" × 6"	250 × 150	273.0 × 168.3	152	/
10" × 8"	250 × 200	273.0 × 219.1	152	215